



SHIELDS COMPLEX

FEATURES

- Black Nitrile Rubber
- 2 textile plies w/ dual wire helix for reinforcement
- Black Chlorprene Cover
- Temp. Range: -20F to +212F

SPECIFICATIONS

SAE J1942 Code F, VW, NVW;
SAE J1527 A1; SAE J2006 R2;
SAE 20R2 B; SAE J20R4 B;
SAE 20R5 B, SAE 30R5,
ISO 7840 A1



ALL IN ONE HOSE FOR INSPECTED VESSELS

Shields Complex is a versatile wire reinforced hose specially designed for inspected vessels. Complex is rated for fuel, vital water and non-vital water systems on boats requiring SAE J1942 hoses. Applications include bilge, coolant, oil and fuel systems using gasoline, gasohol, diesel, bio-diesel, wet exhaust systems, non-potable water systems, engine intake, toilet and holding tank connections.

ORDER INFORMATION

I.D.	mm	O.D.	PLY	WT "C"	BEND RADIUS	WP	50' COIL	12 1/2' (3.8m) LENGTH	10' (3.1m) LENGTH	6 1/4' (1.9m) LENGTH
5/8"	15.9	1"	2	33	1.5	75	16-321-0580	16-321-0584	16-321-0583	16-321-0581
3/4"	19.1	1.19"	2	39	1.5	75	16-321-0340	16-321-0344	16-321-0343	16-321-0341
1"	25.4	1.41"	2	53	2	75	16-321-1000	16-321-1004	16-321-1003	16-321-1001
1 1/8"	28.6	1.56"	2	62	3	75	16-321-1180	16-321-1184	16-321-1183	16-321-1181
1 1/4"	31.8	1.66"	2	64	3	75	16-321-1140	16-321-1144	16-321-1143	16-321-1141
1 1/2"	38.1	1.91"	2	78	3	50	16-321-1120	16-321-1124	16-321-1123	16-321-1121
2"	50.8	2.48"	2	118	5	50	16-321-2000	16-321-2004	16-321-2003	16-321-2001

NOTE: Additional sizes available 150' minimum order

Issue Date - May 2017

Issue Number - sfh2



www.seastarsolutions.com

