

**SEASTAR™**

SUZUKI 4.4L V6

DF300, DF325 and DF350

Dual Prop Applications



Dometic Marine formerly SeaStar Solutions, would like to clarify the steering requirements for the new DF300, DF325 and DF350 Dual Prop engines. Below are the recommended steering options for these engines.

Single Engine Steering Application Options

1. Optimus EPS power steering.
2. Single engine only HC5345-3, HC5358-3 or HC6845S with a PA1200-2HP Power Assist unit and a 1.7–2.4 cubic inch helm of choice — SeaStar PRO Helms are NOT recommended.

Twin Engine Steering Application Options

1. Optimus EPS or 360 power steering.
2. HC6845 Tournament rams plumbed in parallel, Tournament hardware, Tournament tiebar, a PA1200-2HP Power Assist pump, and a 2.4 cubic inch helm of choice — SeaStar PRO helms are NOT recommended.

Triple and Quad Steering Application Options

1. Optimus EPS power steering.
2. For hydraulic options please consult technical services at: SeaStar@Dometic.com or 604-248-3858.

Catamaran Steering Application Options

1. Optimus EPS power steering is highly recommended.
2. Hydraulic HC5375-3 cylinders, a HA5471-2 Liquid Tiebar, SeaStar PRO helm, and SeaStar PRO hose's.

Power Assist Options

The steering loads associated with Dual Prop engines and lower unit physical size requires the use of a PA1200-2HP Power Assist pump.

Contact Us

If you require further information or additional assistance please contact our technical services department at (604) 248-3858 or email us at seastar@dometic.com.